

E4-LE series 60 Hz*

reverse osmosis machine 2,200 to 13,200 gallons per day



Figure 1: E4-LE Series 60 Hz

When you mention reverse osmosis (RO), SUEZ is the first name to come to mind. Our E-series RO machines (Figure 1) are designed for durable operation, high quality product water production, easy installation, and straightforward control.

typical applications

- Process ingredient water
- Rinse water
- Food ingredient water
- Safe drinking water
- Boiler feed water
- Ion exchange pre-treatment

standard economy features (ECN)

- Low energy design reduces electrical requirements and operating costs
- RO Save.Zs*, 1 micron pre-filter
- Automatic inlet shut-off valve
- Permeate and Concentrate flow meters
- Remote machine on/off capability
- Thermal Motor Protection
- Pre-filter, post-filter, primary, and final pressure gauges
- Flow control center including concentrate and recycle valves

deluxe (DLX) features – in addition to ECN features

- Auto flush system
- Low inlet pressure switch
- Digital conductivity meter
- Alarms: Low Inlet Pressure, Motor Starter overload

safety precautions

A Material Safety Data Sheet containing detailed information about this product is available on request.

Find a contact near you by visiting www.suezwatertechnologies.com and clicking on "Contact Us."

*Trademark of SUEZ; may be registered in one or more countries.

©2017 SUEZ. All rights reserved.

Table 1: Operating Parameters

Operating Pressure	100-110 psig (6.9-7.6 bar)
Maximum Recovery	75%
Nominal Rejection	95-98%
Operating Temperature	55-85 °F (13-30 °C)
Minimum Inlet Pressure	30 psig (2 bar)
Design Temperature	77 °F (25 °C)

Table 3: Pump and Motor

Pump Manufacturer	Tonkaflor
Pump Type	Multi-stage, centrifugal
Materials	SS shell/housing, Noryl* internals
Castings	SS inlet/discharge
Motor	3-phase, TEFC, 208-230/460 VAC

Table 2: Materials of Construction

Frame	Painted Carbon Steel
Membrane Elements	AK4040TM
Membrane Housing	Stainless Steel
Inlet Plumbing	Schedule 80 PVC
High Pressure Plumbing	Reinforced rubber hose
Permeate/Concentrate Tubing	Polyethylene, NSF approved
Control Enclosure	NEMA 1
Motor Starters	NEMA 4X
Cartridge Filter	RO, Save, 1 micron

Table 4: E4-LE Specifications - 60 Hz

Model	E4-2200	E4-4400	E4-6600	E4-8800	E4-11000	E4-13200
ECN	1230850	1230855	1230859	1230863	1230867	1230871
DLX	1230852	1230856	1230860	1230864	1230868	1230871
Flow Specifications						
Recovery Range:	50-75%	50-75%	50-75%	50-75%	50-75%	50-75%
Permeate Rate: gpm (m ³ /h)	1.5 (0.3)	3 (0.7)	4.5 (1.0)	6 (1.4)	7.5 (1.7)	9 (2.1)
Concentrate Rate: gpm (m ³ /h)	1.5-0.5 (0.3-0.1)	3.0-1.0 (0.7-0.2)	4.5-1.5 (1-0.3)	6.0-2.0 (1.4-0.5)	7.5-2.5 (1.7-0.6)	9.0-3.0 (2.1-0.7)
Pump and Motor						
Pump Model	SS1809X	SS1809X	SS1809X	SS1809X	SS1812X	SS1812X
Motor: HP (KW)	1.5 (1.1)	1.5 (1.1)	1.5 (1.1)	1.5 (1.1)	2 (1.5)	2 (1.5)
Membrane Elements						
Quantity	1	2	3	4	5	6
Array	1	1-1	1-1-1	1-1-1-1	2-1-1-1	2-2-1-1
Connections						
Inlet: inch (cm)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)
Permeate: inch (cm)	0.5 (1.3)	0.5 (1.3)	0.5 (1.3)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)
Concentrate: inch (cm)	0.5 (1.3)	0.5 (1.3)	0.5 (1.3)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)
Dimensions & Weights						
Height: inch (cm)	50 (127)	50 (127)	55 (139)	55 (139)	60 (152)	60 (152)
Width: inch (cm)	30 (76)	30 (76)	30 (76)	30 (76)	30 (76)	30 (76)
Depth: inch (cm)	20 (51)	20 (51)	20 (51)	26 (66)	26 (66)	26 (66)
Shipping Weight Estimate: lbs. (kg)	170 (77)	185 (83)	215 (98)	235 (107)	325 (147)	345 (156)