TURBIDITY FILTER SYSTEMS 3900 3" SERIES



Standard Features:

Time Clock Control 3" Female Inlet/Outlet Connections Fleck 3900 Lead-Free Brass Valve Motor-Driven Piston-Operated Fiberglass Resin Tank (s) Ports for Pressure Gauges & Sample Valves

Filter Ag media provides an ideal combination of particle shape, size and density making it a good choice where quality water filtration and water conservation are important. Its fractured edges and irregular surface provides a high surface area and complex flow path for efficient removal of suspended matter through out the filter bed typically reducing suspended solids down to the 20 – 40 micron range.

Physical Properties

Color: Mesh Size Bulk Density

Operating Considerations Service Flow Rate Backwash Rate Light grey to near white 12 x 30 24 - 26 lbs/cf

(normal) 5 gpm /sq. ft. 10 gpm/sq. ft.

Model 2000 Filter Shown

PRODUCT SPECIFICATIONS

Model	Media Qty Cubic Feet	Sq. Ft. Bed Area	Media Tank Dia. X Ht	Service Operating Conditions			Media Tank
Series				Continuous Service Flow	PSI Drop	Max Drain Flow. GPM	Diameter x Height
2000	20	7.07	36″ x 72″	35 gpm	6	85	36" x 90"
3000	30	9.61	42″ x 72″	48 gpm	9	100	42" x 100"

Service flow rate is 5 gpm/sq.ft. Intermittent flow rates and /or favorable local conditions may allow higher flow rates

ADDITIONAL OPERATING INFORMATION

For use on potable water only.	Operating Water Temperature Range	Max 100°	Minimum 35°
Not intended to be used to treat water that is micro biologically unsafe or of unknown quality.	Operating Ambient Temperature Range	Max 120°	Minimum 35°
Installation must comply with all state and local codes.	Operating Pressure Range	Max 125 psi	Minimum 20 psi
Tank dimensions are based on fiberglass only. Steel tanks dimensions will vary.	Electrical Requirements	110V-60Hz primary	
Pressure drops are based on clean filter bed.	Feedwater Turbidity	5.0 N.T.U. Max	
Specifications subject to change without notice.			

ACUA SYSTEMS®

Aqua Systems Commercial & Industrial • 114 Vista Parkway • Avon, Indiana 46123 317-272-6715 • 800-997-5492 • Fax 317-272-6728 www.aquasystemsci.com • e-mail: commercialindustrial@aquasystems.com