

# WATER SOFTENING SYSTEMS

## 3900 3" SERIES MULTI UNIT



Model 2000 Softener Shown

### Multi Tanks Standard Features:

- Electronic Controls
- Colored User Alert
- Female Inlet/Outlet Connections
- Lead-Free Brass Control Valves
- No Hard Water By-Pass
- Fiberglass Tanks
- Premium Grade ion Exchange Resin
- Pressure Gauge / Sample Valve Ports

### Optional Features:

- Flow Meter(s)
- Progressive Flow
- Steel & ASME Tanks
- Pumped Brine
- Skid Mounting With Pre-Piping
- Custom Tailoring
- Brine Reclaim
- Auxilliary Outputs

### Custom Configurations Built to User Requirements

Systems can be built to fit a wide range of user applications

### Choice of Brine Tanks (Shown Below)

Type	Dimensions	Salt Cap.	Salt Grid
Blow Molded	24" x 50"	800 lbs	Optional
Rotational Molded	30" x 48"	1200 lbs	Optional
Rotational Molded	39" x 48"	2500 lbs	No
Rotational Molded	42" x 60"	3600 lbs	No
Rotational Molded	50" x 60"	5000 lbs	No

## PRODUCT SPECIFICATIONS (per unit)

Model No.	Media Qty Cubic Feet	Grains of Capacity			Flow @ 15 psi drop	Flow @ 25 psi drop	Media Tank Dia. X H	Max Drain Flow gpm	Brine Tank Dia x H <sup>1</sup>
		15 lbs/cu. ft.	10 lbs/cu. ft.	5 lbs/cu. ft.					
1000	10.0	300000	250000	200000	120 gpm	170 gpm	24" x 72"	12.0	24" x 50"
1500	15.0	450000	375000	300000	160 gpm	215gpm	30" x 72"	20.0	30" x 48"
2000*	20.0	600000	500000	400000	175 gpm	250 gpm	36" x 72"	30.0	39" x 48"
3000*	30.0	900000	750000	600000	195 gpm	260 gpm	42" x 72"	40.0	42" x 60"
4000*	40.0	1,200,000	1,000,000	800000	210 gpm	280 gpm	48" x 72"	50.0	50" x 60"

Exchange capacity based on treating water with 10 grains per gallon total hardness @ 10 gpm per cu. ft. and free of color, odor and turbidity.

\*Minimum salt dosage is 6 lbs. per cu. ft.

1) Size based on 10 lbs. per cu ft. salt dose.

### ADDITIONAL OPERATING INFORMATION

For use on potable water only.  
Not intended to be used to treat water that is micro biologically unsafe or of unknown quality.  
Installation must comply with all state and local codes.  
Tank dimensions are based on fiberglass only. Steel tanks dimensions will vary.  
Specifications subject to change without notice.

Operating Water Temperature Range  
Operating Ambient Temperature Range  
Operating Pressure Range  
Electrical Requirements  
Feedwater Turbidity  
Chlorine  
Iron

Max 100°  
Max 120°  
Max 125 psi

Minimum 35°  
Minimum 35°  
Minimum 20 psi  
24v-60hz  
5.0 N.T.U. Max  
1.0 mg/l Max  
>5 mg/l Consult Aqua Systems



Aqua Systems Commercial & Industrial • 114 Vista Parkway • Avon, Indiana 46123  
317-272-6715 • 800-997-5492 • Fax 317-272-6728  
www.aquasystemsci.com • e-mail: commercialindustrial@aquasystems.com