

WATER SOFTENING SYSTEMS

GEN II 3" SERIES SINGLE UNIT



Model 2000 Softener Shown

Single Tank Standard Features

- Advanced Electronics
- Colored User Alert & Information Screens
- Fiberglass Tanks
- Premium Ion Exchange Resin
- Pre-programmed & prepared for on site assembly
- Seamless Blow Molded or Rotational Molded Brine Tanks
- Pressure Gauge / Sample Valve Ports

3" FPT Lead Free Brass Control Valve

- Single Drive Piston Operated
- Soft Water Brine Refill
- NSF / FDA Approved Black Coating
- Auxiliary Operation Options
 - Alarm Relay Output
 - Control up to two separate relay operations
 - Control Two Separate Auxiliary Valves

Optional Features

- Flow Meter
- Salt Monitor with Alarms
 - Low Salt Level
 - Brine Unused No Draw
- Steel and ASME Tanks
- Choice of Brine Tank Size
- Pumped Brine
- Skid Mounting Pre-Piping
- Custom Tailoring
- Brine Reclaim
- No Hard Water By-Pass Piston

Custom Configurations Built to User Requirements

Systems can be built to fit a wide range of user applications

PRODUCT SPECIFICATIONS

Model No.	Media Qty Cubic Feet	Grains of Capacity			Flow @ 15 psi drop	Flow @ 25 psi drop	Media Tank Dia. x H	Max Drain Flow gpm	Brine Tank Dia x H ¹
		15lb/ Cubic Feet	10lb/ Cubic Feet	5lb/ Cubic Feet					
1000	10	300,000	250,000	200,000	98	126	24" x 72"	13	24" x 50"
1500	15	450,000	375,000	300,000	144	186	30" x 72"	20	30" x 48"
2000	20	600,000	500,000	400,000	172	222	36" x 72"	25	39" x 48"
3000	30	900,000	750,000	600,000	190	244	42" x 72"	40	42" x 60"
4000	40	1,200,000	1,000,000	800,000	194	251	48" x 72"	50	50" x 60"

1) Size based up to 10 lbs. per cu ft. salt dose

ADDITIONAL OPERATING INFORMATION

For use on potable water only.
 Not intended to be used to treat water that is micro biologically unsafe or of unknown quality.
 Installation must comply with all state and local codes.
 Tank dimensions are based on fiberglass only. Steel tanks dimensions will vary.
 Specifications subject to change without notice.

Operating Water Temperature Range
 Operating Ambient Temperature Range
 Operating Pressure Range
 Electrical Requirements
 Feedwater Turbidity
 Chlorine
 Iron

Max 100°
 Max 120°
 Max 125 psi

Minimum 35°
 Minimum 35°
 Minimum 20 psi
 24v-60hz
 5.0 N.T.U. Max
 1.0 mg/l Max
 >5 mg/l Consult Aqua Systems



Aqua Systems Commercial & Industrial • 114 Vista Parkway • Avon, Indiana 46123
 317-272-6715 • 800-997-5492 • Fax 317-272-6728
 www.aquasystemsci.com • e-mail: commercialindustrial@aquasystems.com